



ExxonMobil™ HDPE HD 8660 Series High Density Polyethylene Resin

Product Description

HD 8660 Series are high density hexene copolymers designed to offer superior toughness and stiffness. They are ideally suited for applications that require the optimum balance of low temperature toughness, creep resistance, stiffness, ESCR, and tear properties.

General

Availability ¹	• Latin America	• North America	
Additive	• HD 8660.29: Long Term UV-15 Stabilizer: Yes	• HDP8660.29: Long Term UV-15 Stabilizer: Yes	
Applications	• Industrial Products	• Intermediate Bulk Containers	• Large Agricultural Tanks
Revision Date	• 09/01/2014		

Resin Properties	Typical Value	Unit	Test Based On
Density	0.941	g/cm ³	ASTM D1505
Melt Mass-Flow Rate (MFR) (190°C/2.16 kg)	2.0	g/10 min	ASTM D1238 (mod)

Thermal	Typical Value	Unit	Test Based On
Deflection Temperature Under Load (DTUL) at 66psi - Unannealed	135	°F	ASTM D648
Deflection Temperature Under Load (DTUL) at 264psi - Unannealed	100	°F	ASTM D648
Peak Melting Temperature	264	°F	ASTM D3418

Molded Properties	Typical Value	Unit	Test Based On
Tensile Strength at Yield (2.0 in/min)	2800	psi	ASTM D638
Elongation at Yield (2.0 in/min)	10	%	ASTM D638
Flexural Modulus - 1% Secant	130000	psi	ASTM D790B
Environmental Stress-Crack Resistance			ASTM D1693A
10% Igepal, F50	40	hr	
100% Igepal, F50	560	hr	

Impact	Typical Value	Unit	Test Based On
Impact Strength			ARM
-40°F, 0.125 in	68	ft·lb	
0.250 in	190	ft·lb	

Additional Information

- All physical properties were measured on 3 mm. rotomolded samples unless a different value is shown, except for ESCR, which was measured on compression molded samples.
- Tensile testing was conducted at a crosshead speed of 50 mm/min. The tensile strength reported refers to the maximum stress reached during the test.
- Test procedures may be modified to accommodate operating conditions or facility limitations.

Legal Statement

Contact your ExxonMobil Chemical Customer Service Representative for potential food contact application compliance (e.g. FDA, EU, HPFB).

This product is not intended for use in medical applications and should not be used in any such applications.

Notes

¹ Product may not be available in one or more countries in the identified Availability regions. Please contact your Sales Representative for complete Country Availability.

For additional technical, sales and order assistance: www.exxonmobilchemical.com/ContactUs

Worldwide and the Americas

ExxonMobil Chemical Company
22777 Springwoods Village
Parkway
Spring, TX 77389-1425
USA

Asia Pacific

ExxonMobil Chemical Asia
Pacific
1 HarbourFront Place
#06-00 HarbourFront Tower One
Singapore 098633

Europe, Middle East and Africa

ExxonMobil Chemical Europe
Hermeslaan 2
1831 Machelen, Belgium

exxonmobilchemical.com

Typical properties: these are not to be construed as specifications.

©2022 ExxonMobil. ExxonMobil, the ExxonMobil logo, the interlocking "X" device and other product or service names used herein are trademarks of ExxonMobil, unless indicated otherwise. This document may not be distributed, displayed, copied or altered without ExxonMobil's prior written authorization. To the extent ExxonMobil authorizes distributing, displaying and/or copying of this document, the user may do so only if the document is unaltered and complete, including all of its headers, footers, disclaimers and other information. You may not copy this document to or reproduce it in whole or in part on a website. ExxonMobil does not guarantee the typical (or other) values. Any data included herein is based upon analysis of representative samples and not the actual product shipped. The information in this document relates only to the named product or materials when not in combination with any other product or materials. We based the information on data believed to be reliable on the date compiled, but we do not represent, warrant, or otherwise guarantee, expressly or impliedly, the merchantability, fitness for a particular purpose, freedom from patent infringement, suitability, accuracy, reliability, or completeness of this information or the products, materials or processes described. The user is solely responsible for all determinations regarding any use of material or product and any process in its territories of interest. We expressly disclaim liability for any loss, damage or injury directly or indirectly suffered or incurred as a result of or related to anyone using or relying on any of the information in this document. This document is not an endorsement of any non-ExxonMobil product or process, and we expressly disclaim any contrary implication. The terms "we," "our," "ExxonMobil Chemical" and "ExxonMobil" are each used for convenience, and may include any one or more of ExxonMobil Chemical Company, Exxon Mobil Corporation, or any affiliate either directly or indirectly stewarded.